

1450 SERIES

HEAVY DUTY INSULATED CURTAIN WALL FRAME SYSTEM

DESCRIPTION: NON-THERMALLY BROKEN FLUSH GLAZED SYSTEM. PROFILE DIM: 1-3/4" x 4-1/2" (44.5mm x 114.3mm).

APPLICATION: DESIGNED TO SUIT ALL STANDARD DOORS AND DOOR HARDWARE.

FINISH: MOST PROFILES ARE STOCKED IN #17 CLEAR AND #40 BRONZE ANODIZED. OTHER ANODIZED AND PAINT FINISHES ARE AVAILABLE UPON REQUEST.


STOCK LENGTH: 24'-2" (7.37 METERS).

ASSEMBLY: DESIGNED FOR SCREW PORT AND/OR BRACKET ASSEMBLY.

STRENGTH: REFER TO WIND LOAD CHARTS FOR MAXIMUM ALLOWABLE SPANS.

ANCHORING: REFER TO FABRICATION AND INSTALLATION MANUAL.

GLAZING: 1450 SERIES ACCEPTS SINGLE GLASS, THIS SYSTEM IS TYPICALLY GLAZED FROM THE EXTERIOR, BUT CAN BE GLAZED FROMM THE INTERIOR, REFER TO APPICABLE DETAILS.



Norstar Windows and Doors Ltd.

400 McNeilly Road, Stoney Creek, ON. L8E 5E3 **T** 905-643-9333 **F** 905-643-3633 **W** norstarwindows.com



